

Protective Caps

The Safest Protection for Your
Hirschmann Automotive Connector



HIRSCHMANN
AUTOMOTIVE

DRIVEN BY QUALITY AND INNOVATION

External influences as dust, dirt or water can harm connectors. Hence, we developed caps which protect and stabilize them. The protective caps are designed ergonomically and they close completely. This saves valuable installation space. The simple and secure catch with film hinges ensures a robust and torque-proof position at the housing.

Our protective caps are available for different pole numbers and cable outlets. They can be used for our connectors SealStar 1.2 and 2.8 as well as 1.2 SealStar HMK.



Characteristics:

- one-piece-design with film hinge
- the same dress covers is compatible with multiple connectors Systems (0.63 & 1.2 & 2.8)
- suitable for high pressure and steam cleaning according to IPx9K
- temperature resistance: -40° C to +140° C (objective: up to +150° C)
- ergonomically shaped protective caps for optimal installation
- intuitive assembling


THIS PRODUCT IS AN ACCESSORY OF THE PRODUCT FAMILY 1.2 AND 2.8 SEALSTAR AND 1.2 SEALSTAR HMK.



TECHNICAL PRODUCT INFORMATION

CABLE OUTLET	180°, straight exit designed for nominal width (NW) 4.5 90°, left or right exit designed for nominal width (NW) 4.5/7.5 mounting on both sides
COLOR	black
MATERIAL	PA6
PITCH	6.0 mm
RESISTANCE	according to GS 95024-3-1 (LV 124), MBN 10306 (LV 124), VW 8000 (LV 124)

TEMPERATURE RANGE



ERGONOMIC GRIP AREA FOR OPTIMAL POWER TRANSMISSION



PRODUCT VARIANTS

	CAVITIES	VARIANT	NW	ORDER/ PRODUCT NO.	BOTH SIDE MOUNTING	0.63 SealStar ¹	1.2 SealStar ¹	2.8 SealStar ¹
	2	180°	4.5	707-130-501	N	2way 805-120-... ² 2way 872-857-... ²	-	2way 806-026-... ²
	2	90°	4.5	707-131-501	Y	2way 805-120-... ² 2way 872-857-... ²	-	2way 806-026-... ²
	3	180°	4.5	707-132-501	N	3way 805-121-... ² 3way 872-858-... ² 3way 872-597-... ²	2way 807-872-... ² 2way 805-198-... ²	3way 806-881-... ²
	3	90°	4.5	707-133-501	Y	3way 805-121-... ² 3way 872-858-... ² 3way 872-597-... ²	2way 807-872-... ² 2way 805-198-... ²	3way 806-881-... ²
	4	180°	4.5	707-134-501	N	4way 805-122-... ² 4way 872-859-... ²	3way 807-873-... ² 3way 805-199-... ²	4way 806-880-... ²
	4	90°	4.5	707-135-501	Y	4way 805-122-... ² 4way 872-859-... ²	3way 807-873-... ² 3way 805-199-... ²	4way 806-880-... ²
	5	180°	4.5	707-136-501	N	5way 805-123-... ² 5way 872-860-... ²	4way 807-874-... ² 4way 805-200-... ²	5way 805-992-... ²
	5	90°	4.5	707-137-501	Y	5way 805-123-... ² 5way 872-860-... ²	4way 807-874-... ² 4way 805-200-... ²	5way 805-992-... ²
	5	90°	7.5	707-138-501	Y	5way 805-123-... ² 5way 872-860-... ²	4way 807-874-... ² 4way 805-200-... ²	5way 805-992-... ²

¹ matching Hirschmann Automotive Connector Order/Product No.

² more details in our product specific SealStar flyers

SEEKING MORE DETAILED INFORMATION?
SCAN ME AND VISIT OUR WEBSITE.




ORDER FREE SAMPLES.



**Johannes Ulrich is your Contact
for Individual Questions**

Global Product Manager Low Voltage

 +43 5522 307 1096

 +43 664 386 58 60

 johannes.ulrich@hirschmann-automotive.com



Hirschmann Automotive GmbH

Oberer Paspelsweg 6–8
6830 Rankweil, Austria

www.hirschmann-automotive.com
shop.hirschmann-automotive.com

