2.8 SealStar F Connector

Completely Watertight, Pre-Assembled & Maximum Performance in a Compact Design



DRIVEN BY QUALITY AND INNOVATION

Smaller, stronger, and more efficient – this connector combines compact design with maximum performance. The compact housings are engineered for durability and space savings without sacrificing performance.

Developed with leading OEMs, these connectors offer compatibility with a wide range of contacts, ensuring flexibility and reliability across different applications.



Characteristics:

The 2.8 SealStar is robust and combines the following positive features:

- compliant with test specification LV214
- watertight according to IPx8/IPx9K
- single-wire sealing and robust radial sealing
- CPA (Connector Positioning Assurance)
- convenient and secure connection
- with audible feedback of detent function
- completely pre-assembled product
- locking element either right or left of the protective shroud possible
- primary and secondary locking
- compatible for 2.8 MCP, CTS and MAK contact systems

TECHNICAL PRODUCT INFORMATION

CAVITIES	2 to 8way
TERMINALS/CONTACTS	MCP 2.8 (TE Connectivity) CTS 2.8 (Aptiv) MAK 2.8 (Lear)
PITCH	5.0 mm
WIRE SIZE RANGE	max. 2.50 mm ²
LV214 or TLF0214	TK31/SG4
USCAR2	S2 v S3 ²
IP-CODE	IPx8/IPx9K ²

TEMPERATURE RANGE +120° C VIBRATION



PRODUCT VARIANTS: FEMALE HOUSING



2WAY



3WAY



4WAY



5WAY



8

female

2

yes

yes

А

В

807-871-521



CAVITIES

CPA

TYPE OF PRODUCT

STANDARD PRODUCT

CODING OF PRODUCT

ORDER/PRODUCT NO.

OTHER CODINGS AVAILABLE

NUMBER OF TERMINAL ROWS

8WAY

¹ Tested wit	h the temper	ature collective	e from LV124
-------------------------	--------------	------------------	--------------

² Protective Cap recommended

CAVITIES	2
TYPE OF PRODUCT	female
NUMBER OF TERMINAL ROWS	1
CPA	yes
STANDARD PRODUCT	yes
CODING OF PRODUCT	А
OTHER CODINGS AVAILABLE	B, C
ORDER/PRODUCT NO.	807-872-511

CAVITIES	3
TYPE OF PRODUCT	female
NUMBER OF TERMINAL ROWS	1
CPA	yes
STANDARD PRODUCT	yes
CODING OF PRODUCT	А
OTHER CODINGS AVAILABLE	В
ORDER/PRODUCT NO.	807-873-511

CAVITIES	4	
TYPE OF PRODUCT	female	
NUMBER OF TERMINAL ROWS	1	
СРА	yes	
STANDARD PRODUCT	yes	
CODING OF PRODUCT	А	
OTHER CODINGS AVAILABLE	В	
ORDER/PRODUCT NO.	807-874-511	

¹ Tested	with	the	tempe	rature	collective	from	I V124

SEEKING MORE DETAILED INFORMATION? SCAN ME AND VISIT OUR WEBSITE.



ORDER FREE SAMPLES.



Johannes Ulrich is your Contact for Individual Questions

Global Product Manager Low Voltag



- +43 664 386 58 60
- johannes.ulrich@hirschmann-automotive.com

Hirschmann Automotive GmbH Oberer Paspelsweg 6–8 6830 Rankweil, Austria

www.hirschmann-automotive.com shop.hirschmann-automotive.com



3/2025 Subject to change. All rights reserved by Hirschmann Automotive GmbH.